

• High efficiency design results in low power consumption.



| GFM-200        | A                         | <b>N</b> FAST         | SAFE   |           |  |
|----------------|---------------------------|-----------------------|--|-----------|--|
| Specifications |                           |                       |  |           |  |
| ELECTRICAL     | Voltage Test Type:        |                       | AC.  |           |  |
|                | Output:                   |                       | 0-200 Amps $\pm 3\%$ - short circuit to 12.5m $\Omega$ .       |           |  |
|                | Voltage:                  |                       | 5 Volts max at open circuit.                                   |           |  |
|                | Meters:                   |                       | 0-6V AC $\pm$ 3% full scale.<br>0-200A AC $\pm$ 3% full scale. |           |  |
| ENVIRONMENTAL  | Operation Temperatur      | peration Temperature: |  | 15-40 °C. |  |
|                | Relative Humidity Range:  |                       | 0-90% non-condensing.  |           |  |
| GENERAL        | Input Power Requirements: |                       | 120 Volts, 50/60 Hz.<br>220, 230 or 240 Available.             |           |  |
|                | Dimensions:               |                       | 11.25(W) x 4.25(H) x 12.00(L) in.                              |           |  |
|                | Weight:                   |                       | 30 Lbs.  |           |  |

650 Gateway Center Way Suite D, San Diego, CA 92102 USA

Toll Free: (800) 748-6224 Tel: (619) 878-9696

