

Switchable Passive Probes

PB470 / PP510


Technical Specification	PB470	PP510
Attenuation Rate	1X / 10X	1X / 10X
Bandwidth	10 X: DC-70 MHz	10 X: DC-100 MHz
Input Impedance	1 MΩ / 10 MΩ	1 MΩ / 10 MΩ
Input Capacitance	1 X: 85 pF-120 pF 10 X: 18.5 pF-22.5 pF	1 X: 85 pF-120 pF 10 X: 18.5 pF-22.5 pF
Input Voltage	1 X: 150V RMS CAT II 10 X: 300V RMS CAT II	1 X: 150V RMS CAT II 10 X: 300V RMS CAT II
Compensation Range	10 pF-35 pF	10 pF-35 pF
Operation Temp	-10 °C - 55 °C	-10 °C - 55 °C
Cable Length	130 cm	130 cm
Weight	55 g	55 g


Subject to change without notice




Scientific Mes-Technik Pvt. Ltd.

B-14, Pologround, Industrial Estate, Indore 452 015, India

 0731-2422330/31/32/33

 0731-2422334

 sales@scientificindia.com

 www.scientificindia.com





Bengaluru 080-23452635


Chennai 044-42054180


Gujarat +917567463752

Hyderabad +917095228811

 bangalore@scientificindia.com

 chennai@scientificindia.com

 gujarat@scientificindia.com

 hyderabad@scientificindia.com


Kolkata +919673162333


Mumbai +919850901735

New Delhi +918889912554

Pune +919850901735

 kolkata@scientificindia.com

 mumbai@scientificindia.com

 ndelhi@scientificindia.com

 pune@scientificindia.com