

Impulse Generator SMIMP10.0-10/700

Impulse Generator is designed for Impulse test requirement as per IEC 62368-1, Table D.1, circuit 1 and as per previous standard IEC 60950-1, table N.1, circuit 1 with high reliability, intelligent control, user-friendly design and many other features. The object of this product is to simulate impulse of voltages induced into telephone wires and coaxial cables in long outdoor cable runs due to lightning strikes to their earthing shield.

Advance Features	
 Impulse test system as per fully compliant with the new standards of IEC 62368-1 and previous standard IEC 60950-1 Easy Programmable operation option by a key setting. BNC port to measure output voltage of waveform. 	 Large 7 Inch LCD Touch Screen Display with intelligent control panel. Impulse tester with fully automatic as well as manual trigger option. Built-in RS485, RJ45 & USB interface for remote operation. User friendly software for PC operation
Other Features	
 Out put terminals: High & Return at front 1000:1 voltage devider to measure output voltage of waveform at front BNC port Safety interlock at rear, shorted for normal operation 	 Deliverables: Impulse generator User manual High voltage test leads, 02 Factory calibration certificate ISO17025 accredited calibration certificate optionally avaliable

Technical Specifications

Parameters	SMIMP10.0-10/700
Output Voltage	0.3 ~ 10 kV ± 10%
Wave form parameter of	10 μs ± 30%
Open -circuit rise time	
Wave form parameter of	700 μs ± 20%
Open -circuit pulse	
duration	
Polarity	Positive / Negative
Trigger Mode	AUTO/MANUAL
Output impedance	40 Ω
Impulse count	1~999
Impulse interval	5 ~ 999 s
Display Screen	7 Inches LCD color touch screen
Mains supply	AC 230 V,±10%, 50 Hz /60 Hz
Communication Mode	RS485, RJ45 & USB
Ambient Temperature	15ºC to 45ºC
Relative Humidity	45%-75%

